



ORALITE®



MILESTONE H-50

Description

Cylindrical milestone designed to provoke a deterrent effect while reinforcing security measures.

Made of co-polymer material composed of high quality polyethylene and E.V.A providing properties of flexibility, strength and durability against external agents thanks to its U.V treatment.

Uses and Functions

On high-speed roads mainly clearing drivers the vision of divergent zones. You can mark any área with this milestone.

- ✓ Identification: The H-50 manufactured by JOPI are marked in the lower part the month and year of manufacture, EN 12899-3:2007 CE and JOPI
- ✓ Retroreflective Material: The material used is **Oralite 5930M** level III high density White.
- ✓ Colors: The body of the Milestone may be red, yellow, green or blue. (Other colors at the request of the customer)
- ✓ Anchorage Element: The anchoring element supplied by JOPI is composed of a 12.120 threaded metal plug. Inside the Milestone contains a circular disc with a 12x30 protruding screw on the lower part of its central axis, this assembly being an element that joins the metal block.

Installation

The cylindrical Milestone also has a hole in its upper part to facilitate its anchoring. It is designed to insert the corresponding tubular key and be able to tighten it correctly.



ORALITE®

Technical Specifications

MECHANICAL / STRUCTURAL

Measurements: H = 50 cms. Ø = 14 cm

Weight: 640 gr (+/- 10%)

Material: Polyethylene and E.V.A with reflective tape level III **Oralite 5930M**

Cold fragility: 2.8 ± 0.7 N

Vicat softening point: 88,5 °C

Fusion Point: 123 °C

Pantone Colors

The colors belong to these pantones with U.V treatment

- ✓ Yellow P7405-C
- ✓ Green P336-C
- ✓ Red P7621-C
- ✓ Blue P2145-C

Assembly Drawing

